



(19)

(11) Publication number: **04096222 A**

Generated Document.


PATENT ABSTRACTS OF JAPAN(21) Application number: **02207134**(51) Intl. Cl.: **H01L 21/302**(22) Application date: **03.08.90**

<p>(30) Priority:</p> <p>(43) Date of application publication: 27.03.92</p> <p>(84) Designated contracting states:</p>	<p>(71) Applicant: FUJITSU LTD</p> <p>(72) Inventor: AOYAMA ATSUYUKI</p> <p>(74) Representative:</p>
---	--

(54) MANUFACTURE OF SEMICONDUCTOR DEVICE**(57) Abstract:**

PURPOSE: To perform etching of an Si oxide film and an Si nitride film by a dry method without damaging a substrate by etching the Si oxide film and the Si nitride film by exposing these to F-group gas containing specific atoms, and mixed gas of aforesaid F-group gas and H₂O, H₂.

CONSTITUTION: Etching of an Si oxide film 3 and an Si nitride film 4 is performed by exposing these to F-group gas containing F-atoms of HF, F₂, XeF₂ and to mixed gas of aforesaid F-group gas and H₂O, H₂. Etching of a nitride film, an oxide film is performed according to an etching property, thickness of semiconductor constitution materials such as single Si, polySi, a nitride film, an oxide film and the kinds of F-group gas, and the materials around them are made to remain. During an etching process, ultraviolet light is directly applied to F-group gas or a substrate 1. After the etching process, annealing is performed. After etching or annealing processes, again a film 6 is formed. Directly before finishing the etching process, F-group gas is changed to F-group gas having low etching speed of the semiconductor substrate.



COPYRIGHT: (C)1992,JPO&Japio

BEST AVAILABLE COPY